

Rua Doutor Jesuíno Maciel, 1740 Campo Belo
 São Paulo - SP - CEP 04615-005

Fone: + 55 11 5535-0050
www.flexmedia.com.br

SC Fixed Type Attenuators



Item	Code	Descriptions
1	ADAP027	SC/UPC Adapter (Female) <-> SC (Male) SM 10db Attenuation - Simplex
2	ADAP028	SC/UPC Adapter (Female) <-> SC (Male) SM 20db Attenuation - Simplex
3	ADAP039	SC/UPC Adapter(Female) <-> SC/UPC(Male) 3db Attenuation – Simplex

Specifications

Parameter	Doped Fiber Type
Operation Wavelength(nm)	1310 or 1550
Attenuation (dB)	1 - 20
Return Loss (dB)	PC>45, UPC>55, APC>65
Attenuation Accuracy (dB)	1-5Db:+/-0.5dB 6-10dB:+/-1dB 10-20Db:+/-10%
Operation Temperature (°C)	-40 - +70
Storage Temperature (°C)	-40 to +85

Features

- Precise Attenuations value
- Environmentally stability
- Excellent return loss
- Bi-directional
- Doped Fiber Type
- Comply with Telcordia GR-326-CORE and RoHS standard

Applications

- Telecom network
- Ethernet network
- Optical communication equipment

